
## BF300 / BF300SS - Cast Steel / Cast 316 Stainless Steel



Sure Flow Class 300 ASME Flanged basket strainers are available in Cast Steel and Cast Stainless Steel. The screen is in the form of a basket, with a lifting handle, so that all particulate captured and retained by the screen can be easily removed for disposal.



### Notes:

Must specify if for steam service

Manufacturer reserves the right to modify dimensions, materials, or design. Consult factory for certification.

## Construction

Carbon Steel - Body, Cover - ASTM A216 Grade WCB Stainless Steel - Body, Cover - ASTM A351 Grade CF8M All screens are Stainless Steel

Dimensions (Inches)								
Inches	Size Prefix	А	В	С	Blow Off NPT	Basket Removal Clearance	Shipping Weight (LBS)	
2	0200	8 1/2	5 7/16	5 3/8	1	13 1/4	45	
2 1/2	0250	8 11/16	6 7/16	5 3/4	1	15 3/8	65	
3	0300	9 9/16	7	7 1/8	1	17 5/8	81	
4	0400	11 3/4	8 3/16	8 3/8	1	21	135	
6	0600	14 3/4	9 15/16	9 1/8	1	23 3/4	235	
8	0800	18 1/8	11 5/8	12 1/4	1	29 1/8	440	

For BF300 10-inch size and BF300 12-inch size:

BW300 10-inch size and BW300 12-inch size Fabricated Basket Strainers are used.

# **Ordering Information**

Example: Include full description

Size Model Screen (Prefix) **Number Opening** 125 0400 BF300SS

4" Basket Strainer, Cast Stainless Steel, Class 300 ASME Flanges, 1/8" Perf Screen

Operating Pressures and Temperatures						
Туре	Size	psi @ Temp WOG				
BF300	2" - 8"	740 @ 100 °F				
BF300SS	2" - 8"	720 @ 100 °F				

Standard Screens						
Size	Standard	Opening				
2" - 3"	3/64" perf	0.045"				
4" - 8"	1/8" perf	0.125"				







